

Double Side Cooled Module



FF450R08A03P2

Final Data Sheet

V3.0, 2020-05-11

Automotive High Power

1 Features / Description



$V_{CES} = 750 \text{ V}$
 $I_C = 450 \text{ A}$

Typical Applications

- Automotive Applications
- Hybrid Electrical Vehicles (H)EV
- Optimized for automotive applications with DC link voltages up to 450 V and gate driver voltage level of -8 V / +15 V

Electrical Features

- Integrated Current Sensor
- Integrated Temperature Sensor
- Low Inductive Design
- Blocking voltage 750V
- Low Switching Losses
- Short-time extended Operation Temperature
 $T_{vj\text{ op}} = 175^\circ\text{C}$

Mechanical Features

- 2.5kV AC 1min Insulation
- Double sided cooling
- Compact design
- RoHS compliant

Description

The HybridPACK™ DSC S2 is a very compact half-bridge module targeting hybrid and electric vehicles. The module is based on Infineon's long-term experience developing IGBT power modules and implements the EDT2 IGBT generation, which is an automotive Micro-Pattern Trench-Field-Stop cell design optimized for electric drive train applications. The chipset has benchmark current density combined with short circuit ruggedness and increased blocking voltage for reliable inverter operation under harsh environmental conditions. The EDT2 IGBTs also show excellent light load power losses, which helps to improve System efficiency over a real driving cycle. The EDT2 IGBT was optimized for applications with switching frequencies in the range of 10 kHz. Additionally, on-die integrated current sensor and temperature sensor allow precise monitoring of IGBT state. These features enable enhanced protection and intelligent control of the system.

The innovative and small package is designed for Double Sided Cooling (DSC) with superior thermal performance. The low stray inductance and increased blocking voltage support the design of systems with a very high efficiency. Furthermore, new material combinations and assembly technologies enable best thermal and electrical performance at highest reliability and mechanical robustness.

Product Name	Ordering Code
FF450R08A03P2	SP001630036

2 IGBT, Inverter

2.1 Maximum Rated Values

Parameter	Conditions	Symbol	Value	Unit
Collector-emitter voltage	$T_{vj} = 25^{\circ}\text{C}$	V_{CES}	750	V
Implemented collector current		I_{CN}	450	A
Continuous DC collector current	$T_C = 120^{\circ}\text{C}$, $T_{vj\text{ max}} = 175^{\circ}\text{C}$	$I_{C\text{ nom}}$	300	A
Repetitive peak collector current	$t_p = 1\text{ ms}$	I_{CRM}	900	A
Total power dissipation	$T_C = 25^{\circ}\text{C}$, $T_{vj\text{ max}} = 175^{\circ}\text{C}$	P_{tot}	1667	W
Gate-emitter peak voltage		V_{GES}	+/-20	V

2.2 Characteristic Values

			min.	typ.	max.	
Collector-emitter saturation voltage	$I_C = 300\text{ A}$, $V_{GE} = 15\text{ V}$ $I_C = 300\text{ A}$, $V_{GE} = 15\text{ V}$ $I_C = 300\text{ A}$, $V_{GE} = 15\text{ V}$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	$V_{CE\text{ sat}}$		1.20 1.27 1.29	V
Gate threshold voltage	$I_C = 4.85\text{ mA}$, $V_{CE} = V_{GE}$	$T_{vj} = 25^{\circ}\text{C}$	$V_{GE\text{ th}}$	4.90	5.80	6.50 V
Gate charge	$V_{GE} = -8\text{ V} \dots 15\text{ V}$, $V_{CE} = 400\text{ V}$		Q_G		2.15	μC
Internal gate resistor		$T_{vj} = 25^{\circ}\text{C}$	$R_{G\text{ int}}$		2.0	Ω
Input capacitance	$f = 1\text{ MHz}$, $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$	$T_{vj} = 25^{\circ}\text{C}$	C_{ies}		38.5	nF
Reverse transfer capacitance	$f = 1\text{ MHz}$, $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$	$T_{vj} = 25^{\circ}\text{C}$	C_{res}		0.18	nF
Collector-emitter cut-off current	$V_{CE} = 450\text{ V}$, $V_{GE} = 0\text{ V}$	$T_{vj} = 25^{\circ}\text{C}$	I_{CES}			0.1 mA
Gate-emitter leakage current	$V_{CE} = 0\text{ V}$, $V_{GE} = 20\text{ V}$	$T_{vj} = 25^{\circ}\text{C}$	I_{GES}			400 nA
Turn-on delay time, inductive load	$I_C = 300\text{ A}$, $V_{CE} = 400\text{ V}$ $V_{GE} = -8/+15\text{ V}$ $R_{Gon} = 3.6\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	$t_{d\text{ on}}$		0.34 0.36 0.36	μs
Rise time, inductive load	$I_C = 300\text{ A}$, $V_{CE} = 400\text{ V}$ $V_{GE} = -8/+15\text{ V}$ $R_{Gon} = 3.6\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_r		0.06 0.07 0.07	μs
Turn-off delay time, inductive load	$I_C = 300\text{ A}$, $V_{CE} = 400\text{ V}$ $V_{GE} = -8/+15\text{ V}$ $R_{Goff} = 2.4\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	$t_{d\text{ off}}$		0.48 0.54 0.56	μs
Fall time, inductive load	$I_C = 300\text{ A}$, $V_{CE} = 400\text{ V}$ $V_{GE} = -8/+15\text{ V}$ $R_{Goff} = 2.4\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_f		0.07 0.12 0.13	μs
Turn-on energy loss per pulse	$I_C = 300\text{ A}$, $V_{CE} = 400\text{ V}$, $L_S = 25\text{ nH}$ $V_{GE} = -8/+15\text{ V}$, $di/dt = 3400\text{ A}/\mu\text{s}$ ($T_{vj} = 175^{\circ}\text{C}$) $R_{Gon} = 3.6\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{on}		11.5 13.5 14.5	mJ
Turn-off energy loss per pulse	$I_C = 300\text{ A}$, $V_{CE} = 400\text{ V}$, $L_S = 25\text{ nH}$ $V_{GE} = -8/+15\text{ V}$, $du/dt = 3200\text{ V}/\mu\text{s}$ ($T_{vj} = 175^{\circ}\text{C}$) $R_{Goff} = 2.4\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{off}		12.0 15.5 17.0	mJ
SC data	$V_{GE} \leq 15\text{ V}$, $V_{CC} = 400\text{ V}$ $V_{CE\text{ max}} = V_{CES} - L_{SCE} \cdot di/dt$	$t_p \leq 3\ \mu\text{s}$, $T_{vj} = 175^{\circ}\text{C}$	I_{SC}		2000	A
Thermal resistance, junction to case	per IGBT		R_{thJC}		0.090 ¹⁾	K/W
Thermal resistance, case to heatsink	per IGBT $\lambda_{\text{Paste}} = 1\text{ W}/(\text{m}\cdot\text{K})$ / $\lambda_{\text{grease}} = 1\text{ W}/(\text{m}\cdot\text{K})$ Clamping Force $F = 700\text{ N}$		R_{thCH}		0.100 ¹⁾	K/W
Temperature under switching conditions	t_{op} continuous for 10s within a period of 30s, occurrence maximum 3000 times over lifetime		$T_{vj\text{ op}}$	-40 150	150 175	$^{\circ}\text{C}$

¹⁾ with double sided cooling, evaluation according to HybridPACK cool application note

3 Diode, Inverter

3.1 Maximum Rated Values

Parameter	Conditions	Symbol	Value	Unit
Repetitive peak reverse voltage	$T_{vj} = 25^{\circ}\text{C}$	V_{RRM}	750	V
Implemented forward current		I_{FN}	450	A
Continuous DC forward current		I_F	300	A
Repetitive peak forward current	$t_P = 1 \text{ ms}$	I_{FRM}	900	A
I^2t - value	$V_R = 0 \text{ V}$, $t_P = 10 \text{ ms}$, $T_{vj} = 150^{\circ}\text{C}$	I^2t	8500	A^2s

3.2 Characteristic Values

			min.	typ.	max.	
Forward voltage	$I_F = 300 \text{ A}$, $V_{GE} = 0 \text{ V}$ $I_F = 300 \text{ A}$, $V_{GE} = 0 \text{ V}$ $I_F = 300 \text{ A}$, $V_{GE} = 0 \text{ V}$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	V_F	1.55 1.45 1.40	1.83	V
Peak reverse recovery current	$I_F = 300 \text{ A}$, $-di_F/dt = 3400 \text{ A}/\mu\text{s}$ ($T_{vj} = 175^{\circ}\text{C}$) $V_R = 400 \text{ V}$ $V_{GE} = -8 \text{ V}$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	I_{RM}	170 235 250		A
Recovered charge	$I_F = 300 \text{ A}$, $-di_F/dt = 3400 \text{ A}/\mu\text{s}$ ($T_{vj} = 175^{\circ}\text{C}$) $V_R = 400 \text{ V}$ $V_{GE} = -8 \text{ V}$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	Q_r	12.0 26.0 31.0		μC
Reverse recovery energy	$I_F = 300 \text{ A}$, $-di_F/dt = 3400 \text{ A}/\mu\text{s}$ ($T_{vj} = 175^{\circ}\text{C}$) $V_R = 400 \text{ V}$ $V_{GE} = -8 \text{ V}$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{rec}	2.90 6.60 8.00		mJ
Thermal resistance, junction to case	per diode		R_{thJC}		0.145 ¹⁾	K/W
Thermal resistance, case to heatsink	per diode $\lambda_{Paste} = 1 \text{ W}/(\text{m}\cdot\text{K})$ / $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$ Clamping Force $F = 700\text{N}$		R_{thCH}	0.140 ¹⁾		K/W
Temperature under switching conditions	t_{op} continuous for 10s within a period of 30s, occurrence maximum 3000 times over lifetime		$T_{vj op}$	-40 150	150 175	$^{\circ}\text{C}$

4 Module

Parameter	Conditions	Symbol	Value			Unit
Isolation test voltage	RMS, f = 50 Hz, t = 1 min.	V _{ISOL}	2.5			kV
Material of module baseplate			Cu			
Internal isolation	basic insulation (class 1, IEC 61140)		Al ₂ O ₃			
Creepage distance	terminal to heatsink terminal to terminal	d _{Creep}	3.5			mm
Clearance	terminal to heatsink terminal to terminal	d _{Clear}	3.5			mm
Comperative tracking index		CTI	> 600			
			min.	typ.	max.	
Stray inductance module		L _{sCE}		15		nH
Storage temperature		T _{stg}	-40		125	°C
Terminal connection torque	Screw M5	M		-		Nm
Mounting force per clamp		F		-	750	N
Weight		G		31		g

5 Temperature Sensor

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_{TS} = 0.22 \text{ mA}$, $T_{vj} = 25^{\circ}\text{C}$	V_{TS}	2.220 ²⁾	2.280	2.340 ²⁾	V
temperature coefficient (tcr)	$I_{TS} = 0.22 \text{ mA}$	TC_{TS}		-5.50		mV/K

¹⁾ with double sided cooling, evaluation according to HybridPACK cool application note

²⁾ Verified by design, not by test

6 Current Sensor

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Output voltage	$V_{CE} = 1.85 \text{ V}$, $I_C = 900 \text{ A}$ $R_{sense} = 2.40 \text{ } \Omega$, $T_{vj} = 25^\circ\text{C}$ $V_{GE} = 15 \text{ V}$	V_{sense}		0.55		V


7 Customized

			min.	typ.	max.	
Current Sensor Output Current	$I_C = 100 \text{ A}$, $T_{vj} = 175^\circ\text{C}$, evaluation according to HybridPACK™ DSC application note	I_{cs}	80	100	120	mA

8 Characteristics Diagrams


output characteristic IGBT, Inverter (typical)

$I_C = f(V_{CE})$
 $V_{GE} = 15 \text{ V}$




output characteristic IGBT, Inverter (typical)

$I_C = f(V_{CE})$
 $T_{vj} = 175^\circ\text{C}$




transfer characteristic IGBT, Inverter (typical)

$I_C = f(V_{GE})$
 $V_{CE} = 20 \text{ V}$



switching losses IGBT, Inverter (typical)


$E_{on} = f(I_C)$, $E_{off} = f(I_C)$
 $V_{GE} = -8 / +15 \text{ V}$, $R_{Gon} = 3.6 \Omega$, $R_{Goff} = 2.4 \Omega$, $V_{CE} = 400 \text{ V}$



switching losses IGBT, Inverter (typical)


$$E_{on} = f(R_G), E_{off} = f(R_G)$$

$$V_{GE} = -8 / +15 \text{ V}, I_C = 300 \text{ A}, V_{CE} = 400 \text{ V}$$



transient thermal impedance IGBT, Inverter


$$Z_{thJH} = f(t)$$



reverse bias safe operating area IGBT, Inverter (RBSOA)


$$I_C = f(V_{CE})$$

$$V_{GE} = \pm 15 \text{ V}, R_{Goff} = 2.4 \Omega, T_{vj} = 175^\circ\text{C}$$



forward characteristic of Diode, Inverter (typical)


$$I_F = f(V_F)$$



switching losses Diode, Inverter (typical)

$$E_{rec} = f(I_F)$$


$$R_{Gon} = 3.6 \, \Omega, V_{CE} = 400 \, V$$



switching losses Diode, Inverter (typical)


$$E_{rec} = f(R_G)$$

$$I_F = 300 \, A, V_{CE} = 400 \, V$$




transient thermal impedance Diode, Inverter

$$Z_{thJH} = f(t)$$




9 Circuit diagram



Pin Number	Symbol	I/O	Function
1	P	DC Supply (+)	Positive Supply
2	N	DC Supply (-)	Negative Supply
3	U	AC Output	U Phase Output
4	T+L	Input	Temperature Sensor Plus Low Side
5	T-L	Output	Temperature Sensor Minus Low Side
6	EL	Output	IGBT Emitter Output Low Side
7	CSL	Output	IGBT Current Sensor Output Low Side
8	GL	Input	Gate Input Low Side
9	T+H	Input	Temperature Sensor Plus High Side
10	T-H	Output	Temperature Sensor Minus High Side
11	EH	Output	IGBT Emitter Output High Side
12	CSH	Output	IGBT Current Sensor output High Side
13	GH	Input	Gate Input High Side
14	PS	Output	P-Terminal Voltage Sensing / IGBT Collector Output

10 Package outlines



Drawing: Z8B0017254.2 POL 000 09	Drawing according to ISO 8015	General tolerances: ISO 2768-mK
-------------------------------------	----------------------------------	------------------------------------

Revision History

Major changes since previous revision

Revision History

Reference	Date	Description
V2.0	2018-12-06	-
V2.1	2020-04-16	Correction of package outlines
V3.0	2020-05-11	Final datasheet

Terms & Conditions of usage

Edition 2018-08-01

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2018 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (<http://www.infineon.com>)

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

These components are not designed for "special applications" that demand extremely high reliability or safety such as aerospace, defense or life support devices or systems (Class III medical devices). If you intend to use the components in any of these special applications, please contact your local representative at International Rectifier HiRel Products, Inc. or the Infineon support (<https://www.infineon.com/support>) to review product requirements and reliability testing.

Infineon Technologies components may be used in special applications only with the express written approval of Infineon Technologies. Class III medical devices are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Trademarks

Trademarks of Infineon Technologies AG

AURIX™, C166™, CanPAK™, CIPOS™, CIPURSE™, EconoPACK™, CoolMOS™, CoolSET™, CORECONTROL™, CROSSAVE™, DAVE™, DI-POL™, EasyPIM™, EconoBRIDGE™, EconoDUAL™, EconoPIM™, EconoPACK™, EiceDRIVER™, eupec™, FCOS™, HITFET™, HybridPACK™, I²RF™, ISOFACE™, IsoPACK™, MIPAQ™, ModSTACK™, my-d™, NovalithIC™, OptiMOS™, ORIGA™, POWERCODE™, PRIMARION™, PrimePACK™, PrimeSTACK™, PRO-SIL™, PROFET™, RASIC™, ReverSave™, SatRIC™, SIEGET™, SINDRION™, SIPMOS™, SmartLEWIS™, SOLID FLASH™, TEMPFET™, thinQ!™, TRENCHSTOP™, TriCore™.

Other Trademarks

Advance Design System™ (ADS) of Agilent Technologies, AMBA™, ARM™, MULTI-ICE™, KEIL™, PRIMECELL™, REALVIEW™, THUMB™, μVision™ of ARM Limited, UK. AUTOSAR™ is licensed by AUTOSAR development partnership. Bluetooth™ of Bluetooth SIG Inc. CAT-iq™ of DECT Forum. COLOSSUS™, FirstGPS™ of Trimble Navigation Ltd. EMV™ of EMVCo, LLC (Visa Holdings Inc.). EPCOS™ of Epcos AG. FLEXGO™ of Microsoft Corporation. FlexRay™ is licensed by FlexRay Consortium. HYPERTERMINAL™ of Hilgraeve Incorporated. IEC™ of Commission Electrotechnique Internationale. IrDA™ of Infrared Data Association Corporation. ISO™ of INTERNATIONAL ORGANIZATION FOR STANDARDIZATION. MATLAB™ of MathWorks, Inc. MAXIM™ of Maxim Integrated Products, Inc. MICROTEC™, NUCLEUS™ of Mentor Graphics Corporation. MIPI™ of MIPI Alliance, Inc. MIPS™ of MIPS Technologies, Inc., USA. muRata™ of MURATA MANUFACTURING CO., MICROWAVE OFFICE™ (MWO) of Applied Wave Research Inc., OmniVision™ of OmniVision Technologies, Inc. Openwave™ Openwave Systems Inc. RED HAT™ Red Hat, Inc. RFMD™ RF Micro Devices, Inc. SIRIUS™ of Sirius Satellite Radio Inc. SOLARIS™ of Sun Microsystems, Inc. SPANSION™ of Spansion LLC Ltd. Symbian™ of Symbian Software Limited. TAIYO YUDEN™ of Taiyo Yuden Co. TEAKLITE™ of CEVA, Inc. TEKTRONIX™ of Tektronix Inc. TOKO™ of TOKO KABUSHIKI KAISHA TA. UNIX™ of X/Open Company Limited. VERILOG™, PALLADIUM™ of Cadence Design Systems, Inc. VLYNQ™ of Texas Instruments Incorporated. VXWORKS™, WIND RIVER™ of WIND RIVER SYSTEMS, INC. ZETEX™ of Diodes Zetex Limited.

Last update

2011-11-11

www.infineon.com